



RAY CAMP COMPANY

LIQUID FILTRATION



404-766-4940

Standard and Custom Bags

8409 Tatum Rd. Palmetto, GA 30268 / Tel 404-766-4940 / Fax 404-766-0008

sales@raycamp.com / www.raycamp.com

Flange and Ring Type Bags



Size 1

Fits all standard-length housings made by:
Eaton,
FSI,
GAF,
Pentair,
Rosedale,
Strainrite

Area: 2.5 Sq. Ft.
Diameter: 7.05"
Length: 16.5"



Size PC2

Fits Cuno
Model PC2
housings:

Area: 5.0 Sq. Ft.
Diameter: 9.0"
Length: 30.0"



Size C2

Fits all Commercial-Parker filters standard-length housings:

Area: 4.4 Sq. Ft.
Diameter: 7.31"
Length: 32.0"



Size 2

Fits all double-length housings made by:
Eaton,
FSI,
GAF,
Pentair,
Rosedale,
Strainrite

Area: 4.4 Sq. Ft.
Diameter: 7.31"
Length: 32.0"



Size 3

Fits the following housings:
Eaton,
FSI,
Pentair,
Rosedale Model 4-6

Area: 0.8 Sq. Ft.
Diameter: 4.12"
Length: 9.0"



Size PC1

Fits Cuno
Model PC1 housings:

Area: 2.5 Sq. Ft.
Diameter: 9.0"
Length: 20.0"



Size C1

Fits all Commercial-Parker filters standard-length housings:

Area: 2.0 Sq. Ft.
Diameter: 7.31"
Length: 16.5"



Size 4

Fits the following housings:
Eaton,
FSI Model FS-35,
Pentair,
Rosedale Model 4-12

Area: 1.3 Sq. Ft.
Diameter: 4.12"
Length: 14.0"

Flange and Ring Type Bags



Size 12

Fits Rosedale
Model LLC-8-30:

Area: 5.6 Sq. Ft.
Diameter: 8-3/8"
Length: 32"

Size 7

Fits Pentair,
Rosedale
Model 612:

Area: 1.3 Sq. Ft.
Diameter: 5.6"
Length: 15"

Size 8

Fits Pentair,
Rosedale
Model 618:

Area: 2.0 Sq. Ft.
Diameter: 5.6"
Length: 32"

Size 9

Fits Pentair,
Rosedale
Model 630:

Area: 3.3 Sq. Ft.
Diameter: 5.6"
Length: 32"

RP1

Fits Ronning
Petter Size 1:

Area: 3.5 Sq. Ft.
Diameter: 8"
Length: 30"

RP2

Diameter: 8"
Length: 40"

Tie-On and Special Bags

Available in standard and custom designs
With or without drawstrings in a variety of sizes



How To Order Filter Bags

Build an ordering code as shown in this example.

Example: **PE-25 - P - 7 - S - H**

FIBER AND MICRON RATINGS

Felt, polyester = **PE**
 Microns: 1, 3, 5, 10, 25, 50, 75, 100, 200

Felt, polypropylene = **PO**
 Microns: 1, 3, 5, 10, 25, 50, 100, 200

Mesh, monofilament = **NMO**
 Microns: 1, 5, 10, 25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 400, 600, 800, 1000, 1200

Mesh, monofilament polypropylene = **PMO**
 Microns: 150, 200, 250, 300, 400, 600, 800

Mesh, multifilament polyester = **PEM**
 Microns: 75, 100, 125, 150, 200, 250, 300, 400, 600, 800, 1000, 1500

Felt, Nomex = **HT**
 Microns: 1, 5, 10, 25, 50, 100

Polypropylene, micro fiber = **POMF**
 Microns: .5A, 1A, 2A, 10A, 25A

Polyester, micro fiber = **PEMF**
 Microns: 1, 2.5, 5, 10, 25

Graded Density = **GD**
 Series: 523, 525, 527, 529

BAG FINISH OR COVER

None (standard) = **P**
 Fiber-free glazed, or singed finish = **G**
 Polyester multifilament mesh cover = **PEM**
 Spun-bonded nylon cover (Cerex) = **C**
 Nylon multifilament mesh cover = **NM**

OPTIONS

H = Handle
B = Binding
WE = Welded

BAG STYLE

S = Carbon steel plated ring
SS = Stainless steel ring
PP = Polypropylene ring
T = Drawstring
R = No ring
P = Polypropylene flange

POL = Polypropylene flange
PEL = Polyester flange
NYL = Nylon flange
POSS = Polypropylene flange
PESS = Polyester flange
NYSS = Nylon flange

BAG DIMENSIONS

Symbol	Dia. (in.)	Length (in.)	Symbol	Dia. (in.)	Length (in.)
1	7-1/16	x 16-1/2	RP-1	8.0	x 30
2	7-1/16	x 32	RP-2	8.0	x 40
3	4-1/8	x 8	PC-1	9.0	x 20
4	4-1/8	x 14	PC-2	9.0	x 30
5	4.0	x 24	P30	4.0	x 10
7	5-5/8	x 15	P65	4.0	x 23
8	5-5/8	x 21	X1	4-5/16	x 8
9	5-5/8	x 32	X2	4-5/16	x 14
11	8-3/8	x 16-1/2	X01-100	5-7/8	x 21
12	8-3/8	x 32	410	4.6	x 8
C-1	7.31	x 16.5	420	4.6	x 18
C-2	7.31	x 31.0			


Standard Fibers And Micron Ratings

Construction	Fiber	Available Micron Ratings																				
		1	3	5	10	15	25	50	75	100	125	150	175	200	250	300	400	600	800	1000	1200	1500
Felts	Polyester																					
	Polypropylene																					
	HT-High Temp																					
Multifilament Meshes	Polyester																					
	Nylon																					
Monofilament Meshes	Nylon																					
	Polypropylene																					

Compatibility and Temperature Limits For Standard Bag Materials

Fiber	Compatibility With								Temperature - Limitations (max. deg. F)
	Organic Solvents	Animal Vegetable & Petro Oils	Micro-Organisms	Alkalies	Organic Agents	Oxidizing Agents	Mineral Acids		
Polyester	Excellent			Good				300	
Polypropylene	Excellent			Excellent			Good	200	
Nylon	Excellent			Good	Fair	Poor		325	

Bag Size	Surface Area (sq. ft.)	Viscosity (cps)	Correction Factor
		50	4.5
		100	8.3
1	2.0	200	16.6
1 (inner)	1.6	400	27.7
2	4.4	800	50.0
2 (inner)	3.6	1000	56.2
3	0.5	1500	77.2
4	1.0	2000	113.6
7	1.8	4000	161.0
8	2.0	6000	250.0
9	3.4	8000	325.0
12	5.6	10000	430.0



Disclaimer of Warranty
 To the best of our knowledge, the data contained in this publication is correct; however, we do not assume any liability for the accuracy or completeness of the information. Users should perform their own tests to determine final suitability. Final determination of the suitability of any information or product for the use contemplated by any user, the manner of that use, and whether there is any infringement of patents is the sole responsibility of the user.

